



MATERIALS AND FINISH
 SHELL: STEEL OR COPPER ALLOY MATERIAL, Ti/Ni OR Au FINISHED.
 CONNECTOR INSULATOR: PBT THERMOPLASTIC, 30% GLASS FILLED, UL 94V-0 RATED.
 HIGH POWER CONTACT : COPPER ALLOY MATERIAL, GOLD PLATED.
 CONNECTOR WITH SIGNAL CONTACT MATERIAL: COPPER ALLOY , GOLD PLATED.

ELECTRICAL CHARACTERISTICS
 HIGH POWER CONTACT CURRENT RATING: 40 AMPS.
 CONNECTOR WITH SIGNAL CONTACT CURRENT RATING : 5.0 AMPS.
 THE WORKING VOLTAGE: 300V.
 HIGH POWER CONTACT RESISTANCE: 2.7 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE: 1000 V AC FOR 1 MINUTE.
 INSULATION RESISTANCE: 2000 MEGAOHMS MIN.
 TEMPERATURE RATING: -55j ~ +125j.

| | | | | |
|-------------|-----------|----------|---------------|--|
| TOLERANCE : | | WEBSITE | WWW.WINEN.NET | 深圳市特能电子有限公司 SHEN ZHEN WINEN ELECTRONICS CO., LTD. |
| X. ± 0.35 | X'. ± 3' | TEL | 0755-33816873 | |
| .X ± 0.30 | .X'. ± 2' | DATE | | PART NO. |
| .XX ± 0.20 | | DRAWN | | TITLE |
| | | CHECKED | | 7W2 公 电流焊接式传统耦合 |
| | | APPROVED | | SIZE A4 |
| | | | | VERSION A |
| | | | | CUSS NO. |
| | | | | SCALE 1:1 |
| | | | | UNIT MM |
| | | | | SHEET 1/1 |

| | | | | |
|------|----------|-------------|--------|----------|
| REV. | ECN. NO. | DESCRIPTION | ISSUED | APPROVED |
| A | | NEW | | |

| | | | |
|----------------------|--|--------------|--|
| 3rd ANGLE PROJECTION | | CONFIDENTIAL | |
|----------------------|--|--------------|--|